

CLAIMS

I claim:

1. A device for locking a rope in place, comprising
a lock housing with a top, a bottom, and a rear;
- 5 a guide housing positioned within said lock housing, said guide housing
translatably connected to the lock housing such that the guide housing can only move
in the vertical direction;
a first and a second shoe contained within the guide housing such that the rope
passes between them;
- 10 a first means for suspending the first shoe between the top and bottom of the
guide housing, such that the first shoe can move vertically;
a second means for suspending the second shoe between the top and bottom of
the guide housing such that the second shoe can translate vertically and horizontally;
a handle with a locked and unlocked position;
- 15 a first and second cam pivotally mounted on the housing, the handle connected
to the first cam, and the first and second cam operably connected to each other so that
the rotations of the cams are equal, said cams operably connected to the second shoe
such that moving the handle to the locked position causes the second shoe to
translate towards the first shoe without rotation.
- 20
2. The device of claim 1 wherein the first shoe cannot rotate;
3. The device of claim 1 wherein the second shoe cannot rotate;
- 25 4. The device of claim 1 further comprising and automatic closing means
comprising
a guide means that causes the second shoe to close more tightly against the
first shoe when a load is placed on the rope after the lock has been manually closed.
- 30 5. The device of claim 4, where the automatic closing means remains engaged
when the handle is moved to the open position.

6. The device of claim 5 where the automatic closing means remains engaged until the load on the rope is removed.
7. A device for locking a rope in place, comprising
- 5 a lock housing;
a first and a second shoe contained within said housing such that the rope passes between them;
means for suspending the first shoe between the top and bottom of the housing, such that the first shoe can translate towards the top or bottom of the
- 10 housing;
means for suspending the second shoe between the top and bottom of the housing such that the second shoe can translate towards the top or bottom of the housing, and towards or away from the first shoe;
a handle with a locked and unlocked position;
- 15 means for closing the second shoe in response to moving the handle to the locked position such that the second shoe translates towards the first shoe without rotation.
8. The device of claim 7 wherein the first shoe cannot rotate;
- 20 9. The device of claim 7 wherein the second shoe cannot rotate;
10. The device of claim 7 further comprising a means for automatically holding the second shoe in the closed position in response to placing a load on the rope
- 25 while the second shoe is in the closed position.